



Gebelns en gepassiveerd
 Werkdruk koelmantel : max 12 bar
 Barstdruk breekplaat : 0,1 bar
 Koelwater capaciteit : 1 ttr/sec.
 Max drukval : 4 bar

30			
29			
28			
27			
26			
25			
24	1	1/2"	RIS 304
23	2	1"	"
22	3	ø 1/2"	"
21	4	ø 1/2"	"
20	1	ø 1/2"	"
19	1	ø 1/2"	"
18	8	ø 1/2"	"
17	8	ø 1/2"	"
16	8	ø 1/2"	"
15	1	ø 280/200 ø 1/2"	RIS 304
14	1	ø 280 ø 1/2"	"
13	1	ø 280/200 ø 1/2"	"
12	3	ø 185 ø 1/2"	"
11	3	ø 185 ø 1/2"	"
10	2	ø 185 ø 1/2"	"
9	2	ø 185 ø 1/2"	"
8	2	ø 185 ø 1/2"	"
7	2	ø 185 ø 1/2"	"
6	1	ø 280 ø 1/2"	"
5	2	ø 280 ø 1/2"	"
4	1	ø 280 ø 1/2"	"
3	1	ø 280 ø 1/2"	"
2	2	ø 280 ø 1/2"	"
1	1	ø 280 ø 1/2"	"

Wijk. d.d.:
 Wijk. d.d.:
 Wijk. d.d.:
 Datum: /S- /2- 89

Gez.:
 Gez.:
 Gez.:

Benaming: **MENKTANK inhoud 15000 ltr. PVS 304**

Uitg. no.: 23846
 Tek. no.: 23824.1

ALBERING BV
 BUREAU TECHNISCHE TEKENINGEN
 HANNOVERSE WEG 10
 3813 CA GRIJNBURG
 TEL. 050 371906